

# Zetalase XL 3D

<b>System Dimensions</b>	32"W x 52"L x 74"H / 500lbs (mm) 813"W x 1,321"L x 1,880"H / 227kg
<b>Standard Marking Field</b>	250L Focal Lens 6.5" x 6.5" / 165mm x 165mm
<b>3D Dynamic Focus Range</b>	1.57' / 40mm
<b>Standard Max Part Size</b>	30"W x 24"L x 19.5"H or (mm) 762W x 609L x 429H (mm)381W x 1,066L (Using Center Wall Opening)
<b>Laser Type</b>	Ytterbium Fiber
<b>Wavelength (nm)</b>	1062 +/- 3nm
<b>Wattage</b>	20W / 50W
<b>Frequency Range</b>	1 – 500kHz (20W / 50W)
<b>Pulse Duration</b>	Variable, 260ns or 40ns (20W / 50W)
<b>Operative Ambient Temperature Range</b>	7° – 36° C / 45° – 97° F
<b>Cooling</b>	Forced Air
<b>Input Power Requirements</b>	Power Sensing 110-240VAC 50/60Hz
<b>Aiming Beam</b>	Class II Red Diode (635nm)
<b>PC</b>	Integrated Windows 10 PC Included
<b>Air Required</b>	60 – 80 psi
<b>Machine Ports</b>	Diagnostic/USB/VGA/Ethernet
<b>Warranty</b>	36 Month Comprehensive, Unlimited Hours
<b>Documentation (Provided in Digital Format via USB Drive)</b>	System & Software Manuals Laser Settings Guide / Safety Manual Software Video Tutorials
<b>Accessories</b>	Laser Enable Keys (2) Power Cable / USB Drive Class 4 Service Override Interlock Key